

*Our dream and responsibility
to supply customers
with the best sound*



650Watts+650Watts

BA-133

Professional Power Amplifier



Best Sound System from Japan

Specifications

BA-133 Professional Power Amplifier

Max Rated Output Power 2 channel (stereo)	
8 Ω load	400W + 400W
4 Ω load	650W + 650W
2 Ω load	850W + 850W
1 channel (bridged)	
8 Ω load	1300W
4 Ω load	1700W
Frequency Response	10 - 40,000Hz \pm 3dB
Total Harmonic Distortion	0.02%(max) / 100W, 8 Ω at 1kHz
Damping factor	500 / 8 Ω at 400Hz
Residual Hum & Noise	-100dB
Input level	1.1V
Input impedance	20k
Input terminal	XLR connector(2pin: Hot)
Output terminal	Hi current Binding pot Out-SPKON
System operating mode switch (Back panel)	Stereo/Parallel/Bridged
Low pass filter switch (Back panel) Can use for Sub woofer	Cut-off frequency: 65 Hz
Clip Level Indicator	Full wave RMS peak detector
Dimensions (H x W x D)	80mm x 482mm x 450mm
Net Weight	24.5 kg



BIK CO.,LTD.

3-34 YANAKA-CHO, KOSHIGAYA-SHI,
SAITAMA-KEN 343-0856 JAPAN
TEL. +81-48-969-6533 FAX. +81-48-969-6556
URL. <http://www.bik-coltd.jp>
Email. best-sound@bik-coltd.jp